



EP AP ES AS


Mod. 995



EP AP ES AS


Mod. 694 CLAMP

Connection: Male thread x Female thread
MR1 x FR2: 3/8"x1/2" and 1/2"x1/2"


Material:  Stainless steel. PN-160

Seal:  PTFE (Teflon)

Connection: Flange clamp x Flange clamp
DN1 x DN2: 10 x15 to 25 x 25

Material:  Stainless steel. PN-16

Seal:  PTFE (Teflon)

 Silicone's rubber

 Fluoroelastomer (Viton)

 Perfluoroelastomer (FFKM)

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.

Design in accordance with "International Standard ISO 4126-1 Safety Valves".

Depending on version



-60°C to +200°C



36,01 bar to 144,00 bar



Gases

The valve works as an automatic pressure releasing regulator activated by the static pressure existing at the entrance to the valve and is characterized by its ability to open instantly and totally.

Design in accordance with "ASME code section VIII Div.1". Materials according ASME code section II and ASTM. Connections according ISO 2852 standard.

Depending on version



-60°C to +200°C



0,20 bar to 16,00 bar



Steam/Gases/Liquids